SAS-S/SAS-M

Single Animal Scale, Stationary or Mobile

Standard Features

- Swing gate, sliding gate or one slide gate and one swing gate
- 48 in solid kick panel sides
- · Ships assembled
- Mobile or stationary configurations

Specifications

Capacity: 5,000 x 1, 5 k load cell

Warranty

Two-year limited warranty

Approvals:

NTEP CC 99-091

Measurement Canada AM4847



SAS-S shown with two slide gates and enclosure

APPROVALS



Measurement Canada Approved

Part Number/Price

PART #	INSIDE DIMENSIONS	OUTSIDE DIMENSIONS	DESCRIPTION	EST. SHIP WEIGHT	PRICE
171255	34 in x 96 in	(W x L x H) 46.81 x 109 x 97.8 in	SAS-S, one slide gate and one swing gate	2,300 lb	Consult
172378	34 in x 96 in	(W x L x H) 46.81 x 109 x 97.8 in	SAS-S, two swing gates	2,300 lb	Consult
172379	34 in x 96 in	(W x L x H) 46.81 x 109 x 97.8 in	SAS-S, two slide gates	2,300 lb	Consult

Price does not include instrumentation

Options/Accessories

PART #	DESCRIPTION	PRICE
168774	Enclosure, light duty	Consult
172852	RS420 portable stick reader, Allflex with IEC cable, data cable and external power adapter recharger	Consult
173118	Bluetooth® kit for RS420 stick reader	Consult
172854	920i Single Animal Rate of Gain Stationary Unit (SAS-S)	Consult
173139	920i Single Animal Rate of Gain Mobile Unit (SAS-M) weighcenter	Consult
23113	TM-U295 printer	Consult
15547	Blunt end cable for printer to indicator	Consult